

SECTION B-B


| SYMBOL | MILLIMETER | | |
|--------|------------|-------|-------|
| | MIN | NOM | MAX |
| A | - | - | 1.70 |
| A1 | 0.10 | 0.15 | 0.20 |
| A2 | 1.30 | 1.40 | 1.50 |
| b | 0.17 | - | 0.27 |
| b1 | 0.16 | 0.20 | 0.24 |
| c | 0.13 | - | 0.17 |
| c1 | 0.12 | 0.13 | 0.14 |
| D | 13.90 | 14.00 | 14.10 |
| E | 15.80 | 16.00 | 16.20 |
| E1 | 13.90 | 14.00 | 14.10 |
| eB | 15.05 | - | 15.40 |
| e | 0.50BSC | | |
| L | 0.42 | 0.57 | 0.72 |
| L1 | 0.95 | 1.00 | 1.15 |
| θ | 0 | - | 10° |



Note:

1. All dimension are in mm.
2. Dim D & E1 does not include plastic flash;
Flash: Plastic residual around body edge after
dejunk/singulation.
3. Dim b does not include dambar protrusion/intrusion.
4. Plating thickness 0.007mm-0.015mm

| | | | |
|--------|--|---------|--|
| 拟制 | | 复审 | |
| 审核 | | 会签 | |
| | | | |
| | | | |
| 制图 | | 标准化 | |
| 幅面: A4 | | 批准 | |
| | | 比例: 1:1 | |

| | | | |
|---------------------------------------------------------------------------------------|------|------------------------|-------|
| 更改标记 | 更改内容 | 签名 | 日期 |
|  | | | |
| VKXHLQFP100V11_POD 产品外形图名称 | | 图号: VKXHLQFP100V11_POD | |
| | | 单位 | 版本 |
| | | mm | V1.1 |
| | | 第 1 张 | 共 1 张 |

